

PVC Sewer & Drain Pipe

Solid or Perforated

Conforms to ASTM D 2729 and ASTM D 1784, cell class 12454 or 12364

- Standard color of pipe is white
- Product manufactured with one integral solvent-weld bell standard per length
- Pipe is produced in 10-foot overall lengths
- Perforated pipe is manufactured with $\frac{5}{8}$ -inch holes, 5-inches on center and is available in 2-hole and 3-hole configurations

| Catalog Part Number | | Perf Pattern | Trade Size | Dimensions (inches) | | Minimum Wall (inches) | Approximate Weight Per 100' (lbs) | Standard Crate Quality (feet) |
|---------------------|---------------|--------------|------------|---------------------|-------------|-----------------------|-----------------------------------|-------------------------------|
| Solid | Perforated | | | OD (avg) | ID (approx) | | | |
| 2730010 | 2730010FH | 4-8 | 3 | 3.250 | 3.12 | 0.070 | 49 | 500 |
| 2740010 | 2740010FH | 4-8 | 4 | 4.215 | 4.06 | 0.075 | 68 | 570 |
| - | 2740010FH468 | 4-6-8 | | | | | | |
| - | 2740010FH4812 | 4-8-12 | | | | | | |
| 2760010 | 2760010FH | 4-8 | 6 | 6.275 | 6.06 | 0.100 | 135 | 260 |
| - | 2760010FH468 | 4-6-8 | | | | | | |