

## PVC Solvent-Weld Sewer Pipe

- ASTM D 3034 SDR 35 prior to perforation
- Solvent-weld bells
- 10-foot overall lengths
- White or green in color



Trade Size	Part Number	Length (feet)	Solid or Perf Pattern	Average O.D. (inches)	Approximate Weight per 100' (lbs)	Standard Crate Quantity (feet)
<b>Solid-wall - White</b>						
4	3040010	10	Solid	4.215	104	630
	3040020	20				1,260
6	3060010	10	Solid	6.275	236	260
	3060020	20				520
8	3080010	10	Solid	8.400	429	220
<b>Solid-wall - Green</b>						
4	3040010GRN	10	Solid	4.215	104	630
	3040020GRN	20				1,260
6	3060010GRN	10	Solid	6.275	236	260
	3060020GRN	20				520
<b>Perforated - White</b>						
4	3040010FH	10	4-8	4.215	104	630
	3040010FH468		4-6-8			
6	3060010FH	10	4-8	6.275	236	260
	3060010FH468		4-6-8			
<b>Perforated - Green</b>						
4	3040010FHGRN	10	4-8	4.215	104	630
	3040010FH468GRN		4-6-8			
6	3060010FHGRN	10	4-8	6.275	236	260
	3060010FH468GRN		4-6-8			

Perforated pipe, with 5/8-inch holes, 5 inches on center, are available in 2-hole and 3-hole configurations:

2-hole: 4-8 o'clock position - 120° apart

3-hole: 4-6-8 o'clock or position - 60° apart

NOTE: Special orders are non-cancelable, non-returnable and non-refundable.