

PVC DR35 Solvent Weld Sewer Pipe

Solid or Perforated

Conforms to ASTM D 3034 and ASTM D 1784, cell class 12454 or 12364

- Color of pipe is white or green
- Product manufactured with one integral solvent-weld bell standard per length
- Perforated sewer pipe meets the requirements of ASTM D3034 prior to Perforation. Perforated sewer pipe is manufactured with 5/8 -inch holes, 5-inches on center and is available in 2-hole and 3-hole configurations.

Catalog Part Number		Perf Pattern	Trade Size	Color	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight Per 100' (lbs)	Standard Crate Quality (feet)
Solid	Perforated				OD (avg)	ID (approx)			
3040010	3040010FH	4-8	4 x 10'	White	4.215	3.96	0.120	104	630
	3040010FH468	4-6-8							
3040020	-	-	4 x 20'						1,260
3060010	3060010FH	4-8	6 x 10'	White	6.275	5.89	0.180	236	260
	3060010FH468	4-6-8							
3060020	-	-	6 x 20'						520
3080010	-	-	8 x 10'	White	8.400	7.89	.24	429	140
3040010GRN	3040010FHGRN	4-8	4 x 10'	Green	4.215	3.96	0.120	104	630
	3040010FH468GRN	4-6-8							
3040020GRN	-	-	4 x 20'						1,260
3060010GRN	3060010FHGRN	4-8	6 x 10'	Green	6.275	5.89	0.180	236	260
	3060010FH468GRN	4-6-8							
3060020GRN	-	-	6 x 20'						520