

PVC IPS Pressure Pipe Solvent Weld

Conforms to ASTM D 2241 and ASTM D 1784, cell class 12454

- Certified to requirements of ANSI/NSF 14
- Product manufactured with one integral solvent-weld bell standard per length
- Standard overall pipe length is 20'
- Standard color is white



Catalog Part Number	Trade Size	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight Per 100' (lbs)	Standard Crate Quantity (feet)
		OD (avg)	ID (approx)			
PR 160 – SDR 26						
5112520	1¼	1.660	1.52	0.064	21	4,400
5115020	1½	1.900	1.75	0.073	27	3,600
5120020	2	2.375	2.18	0.091	42	2,100
5125020	2½	2.875	2.64	0.110	62	1,460
5130020	3	3.500	3.21	0.135	92	1,500
5140020	4	4.500	4.13	0.173	152	1,140
5160020	6	6.625	6.08	0.255	330	520

PR 200 – SDR 21						
5207520	¾	1.050	0.92	0.060	12	8,000
5210020	1	1.315	1.18	0.063	16	5,600
5212520	1¼	1.660	1.49	0.079	25	4,400
5215020	1½	1.900	1.71	0.090	33	3,600
5220020	2	2.375	2.14	0.113	52	2,100
5225020	2½	2.875	2.58	0.137	76	1,460
5230020	3	3.500	3.15	0.167	113	1,500
5240020	4	4.500	4.05	0.214	186	1,140
5260020	6	6.625	5.96	0.316	405	520

PR 315 – SDR 13.5						
5305020	½	0.840	0.071	0.062	10	7,200

PVC IPS Pressure Pipe Solvent Weld

Conforms to ASTM D 2241 and ASTM D 1784, cell class 12454

- Certified to requirements of ANSI/NSF 14
- Product manufactured with one integral solvent-weld bell standard per length
- Standard overall pipe length is 20'
- Standard color is white



Catalog Part Number	Trade Size	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight Per 100' (lbs)	Standard Crate Quantity (feet)
		OD (avg)	ID (approx)			
PR 100 – SDR 41						
5030020	3	3.500	3.32	0.085	59	1,500
5040020	4	4.500	4.27	0.110	98	1,140
5060020	6	6.625	6.28	0.162	213	520

PR 125 – SDR 32.5						
5525020	2½	2.875	2.69	0.088	50	1,460
5530020	3	3.500	3.27	0.108	74	1,500
5540020	4	4.500	4.21	0.138	122	1,140
5560020	6	6.625	6.19	0.204	266	520