

Rigid Non Metallic Schedule 80 Electrical Conduit

Schedule 80 Electrical Conduit

Heritage Plastics created the long bell for ease and efficiency. In compliance with the industry standards, Heritage Plastics PVC Electrical Conduit is manufactured from PVC compounds complying with the UL651 standards. Our PVC Electrical Conduits are subject to in-process quality control to assure compliance with appropriate manufacturing and performance standards.

- UL 651
- NEMA TC-2
- Sunlight resistant per UL 651
- Listed for 90° C conductors or cable
- Rigid nonmetallic raceway for wires and cables in accordance with the NEC
- Product manufactured with one integral solvent-weld bell standard per length



10' Part No.	20' Part No.	Trade Size	Average O.D. (in)	Minimum Average I.D. (in)	Minimum Wall (in)	Weight Per Foot (lbs)	10 Ft Crate Quantity (ft)
9302	925785	½	0.840	0.502	0.147	0.205	6000
9303	9503	¾	1.050	0.698	0.154	0.278	4400
9304	9504	1	1.315	0.910	0.179	0.410	3600
9305	924298	1 ¼	1.660	1.227	0.191	0.565	3300
9306	9506	1½	1.900	1.446	0.200	0.726	2250
9308	9508	2	2.375	1.881	0.218	1.004	1400
9310	924299	2 ½	2.875	2.250	0.276	1.531	930
9312	9512	3	3.500	2.820	0.300	2.049	880
924024	925941	3 ½	4.000	3.280	0.318	2.499	630
9316	9516	4	4.500	3.737	0.377	3.122	570
9320	9520	5	5.563	4.713	0.375	4.330	380
9324	9524	6	6.625	5.646	0.432	5.954	260
906397	924567	8*	8.625	7.455	0.500	9.042	140

Meets or exceeds the requirements of NEMA TC 2 and UL 651 for Schedule 80 Conduit.

* UL 651 does not include 8"



Intertek