

# Solvent Weld IPS PVC

## Pressure Rated Pipe

Conforms to ASTM D 1785 and ASTM D 1784, cell class 12454

- Certified to requirements of ANSI/NSF 61
- Product manufactured with one integral solvent-weld bell standard per length
- All pipe is produced in 20-foot overall lengths
- Standard coloring of Schedule 40 pressure pipe is white
- 1½", 2", 3", 4", 6", 8" Schedule 40 products also conform to the Drain, Waste & Vent (DWV) standard ASTM D 2665



Part Number	Trade Size	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight Per 100' (lbs)	Water Pressure Rating (psi)	Standard Crate Quantity (feet)
		O.D. (avg)	I.D. (approx)				
<b>SCHEDULE 40</b>							
5405020	½	0.840	0.61	0.109	16	600	7,200
5407520	¾	1.050	0.81	0.113	22	480	8,000
5410020	1	1.315	1.03	0.133	32	450	5,600
5412520	1¼	1.660	1.35	0.140	43	370	4,400
5415020	1½	1.900	1.59	0.145	52	330	3,600
5420020	2	2.375	2.05	0.154	69	280	2,100
5425020	2½	2.875	2.44	0.203	110	300	1,460
5430020	3	3.500	3.04	0.216	144	260	1,500
5440020	4	4.500	4.00	0.237	205	220	1,140
5450020	5	5.563	5.02	0.258	278	190	760
5460020	6	6.625	6.03	0.280	361	180	520
5480020	8	8.625	7.94	0.322	559	160	300

# Solvent Weld IPS PVC

## Pressure Rated Pipe

Conforms to ASTM D 2241 and ASTM D 1784, cell class 12454

- Certified to requirements of ANSI/NSF 61
- Product manufactured with one integral solvent-weld bell standard per length
- All pipe is produced in 20-foot overall lengths
- Standard coloring of pipe is white



Part Number	Trade Size	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight Per 100' (lbs)	Standard Crate Quantity (feet)
		O.D. (avg)	I.D. (approx)			
<b>PR 160 – SDR 26</b>						
5112520	1¼	1.660	1.52	0.064	21	4,400
5115020	1½	1.900	1.75	0.073	27	3,600
5120020	2	2.375	2.18	0.091	42	2,100
5125020	2½	2.875	2.64	0.110	62	1,460
5130020	3	3.500	3.21	0.135	92	1,500
5140020	4	4.500	4.13	0.173	152	1,140
5150020	5	5.563	5.11	0.214	232	760
5160020	6	6.625	6.08	0.255	330	520
5480020	8	8.625	7.94	0.322	559	300

<b>PR 200 - SDR 21</b>						
5207520	¾	1.050	0.92	0.060	12	8,000
5210020	1	1.315	1.18	0.063	16	5,600
5212520	1¼	1.660	1.49	0.079	25	4,400
5215020	1½	1.900	1.71	0.090	33	3,600
5220020	2	2.375	2.14	0.113	52	2,100
5225020	2½	2.875	2.58	0.137	76	1,460
5230020	3	3.500	3.15	0.167	113	1,500
5240020	4	4.500	4.05	0.214	186	1,140
5260020	6	6.625	5.96	0.316	405	520
5280020	8	8.625	7.76	0.410	684	300

<b>PR 315 – SDR 13.5</b>						
5305020	½	0.840	0.071	0.062	10	7,200