

Solvent Weld IPS PVC

Pressure Rated Pipe

Conforms to ASTM D 2241 and ASTM D 1784, cell class 12454

- Certified to requirements of ANSI/NSF 61
- Product manufactured with one integral solvent-weld bell standard per length
- All pipe is produced in 20-foot overall lengths
- Standard coloring of pipe is white



Part Number	Trade Size	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight Per 100' (lbs)	Standard Crate Quantity (feet)
		O.D. (avg)	I.D. (approx)			
PR 63 – SDR 64						
5980020	8	8.625	8.34	0.135	233	300

PR 100 – SDR 41						
5030020	3	3.500	3.32	0.085	59	1,500
5040020	4	4.500	4.27	0.110	98	1,140
5050020	5	5.563	5.27	0.136	150	760
5060020	6	6.625	6.28	0.162	213	520
5080020	8	8.625	8.18	0.210	369	300

PR 125 – SDR 32.5						
5512520	1¼	1.660	1.53	0.060	19	4,400
5515020	1½	1.900	1.77	0.060	22	3,600
5520020	2	2.375	2.22	0.073	34	2,100
5525020	2½	2.875	2.69	0.088	50	1,460
5530020	3	3.500	3.27	0.108	74	1,500
5540020	4	4.500	4.21	0.138	122	1,140
5550020	5	5.563	5.20	0.171	187	760
5560020	6	6.625	6.19	0.204	266	520
5580020	8	8.625	8.06	0.265	450	300