

Gasketed PIP PVC

Pressure Rated Pipe

Conforms to ASTM D 2241 and ASTM D 1784, cell class 12454

Gasket conforms to ASTM F 477

- Product manufactured with one integral gasketed bell standard per length
- All pipe is produced in 20-foot overall lengths
- Standard coloring of pipe is white
- Each spigot end is beveled to facilitate assembly and reference marked to indicate proper insertion depth

Part Number	Trade Size	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight Per 100' (lbs)	Standard Crate Quantity (feet)
		O.D. (avg)	I.D. (approx)			
PR 80 – SDR 51						
1460020G	6	6.140	5.89	0.120	150	640
1480020G	8	8.160	7.82	0.160	267	360
14100020G	10	10.200	9.78	0.200	418	240
14120020G	12	12.240	11.73	0.240	604	160
14150020G	15	15.300	14.66	0.300	945	120

PR 100 – SDR 41						
1560020G	6	6.140	5.82	0.150	187	640
1580020G	8	8.160	7.74	0.199	330	360
15100020G	10	10.200	9.67	0.249	518	240
15120020G	12	12.240	11.61	0.299	748	160
15150020G	15	15.300	14.51	0.373	1,169	120