

# PVC Schedule 40 Pressure Pipe/DWV

Conforms to ASTM D 1785 and ASTM D 1784, cell class 12454

- Certified to requirements of ANSI/NSF 14
- Product manufactured with one integral solvent-weld bell standard per length
- Standard overall pipe length is 20' or 10'
- Standard color is white
- 1½", 2", 3", 4", 6"-12" also conform to the Drain, Waste & Vent (DWV) standard ASTM D 2665
- 2" – 12" also conform to standard ASTM F480



20' Catalog Part Number	10' Catalog Part Number	Trade Size	Dimensions (inches)		Minimum Wall (inches)	Approximate Weight Per 100' (lbs)	Water Pressure Rating (psi)	Standard 20' Crate Quality (feet)
			OD (avg)	ID (approx)				
5405020	5405010	½	0.840	0.61	0.109	16	600	7,200
5407520	5407510	¾	1.050	0.81	0.113	22	480	8,000
5410020	5410010	1	1.315	1.03	0.133	32	450	5,600
5412520	5412510	1¼	1.660	1.35	0.140	43	370	4,400
5415020	5415010	1½	1.900	1.59	0.145	52	330	3,600
5420020	5420010	2	2.375	2.05	0.154	69	280	2,100
5425020	5425010	2½	2.875	2.44	0.203	110	300	1,460
5430020	5430010	3	3.500	3.04	0.216	144	260	1,500
5440020	5440010	4	4.500	4.00	0.237	205	220	1,140
5450020	5450010	5	5.563	5.02	0.258	278	190	760
5460020	5460010	6	6.625	6.03	0.280	361	180	520
5480020	5480010	8	8.625	7.94	0.322	559	160	300
54100020	-	10	10.750	10.02	0.365	770	140	80
54120020	-	12	12.750	11.94	0.406	1,017	130	60