

PVC IPS Solvent Weld Pressure Pipe - West

Conforms to ASTM D 2241

- Certified to requirements of ANSI/NSF 61
- Product manufactured with one integral solvent-weld bell per length
- Standard overall pipe length is 20-feet
- Standard color is white



| Trade Size | Part Number | Dimensions (in) | | Minimum Wall Thickness (in) | Approximate Weight per 100' (lbs) | Crate Quantity (ft) |
|---|-------------|-----------------|-----------|-----------------------------|-----------------------------------|---------------------|
| | | Avg OD | Approx ID | | | |
| SDR 26 - Pressure Rating 160 psi | | | | | | |
| 1¼ | 5112520 | 1.660 | 1.52 | 0.064 | 21 | 4,400 |
| 1½ | 5115020 | 1.900 | 1.75 | 0.073 | 27 | 3,600 |
| 2 | 5120020 | 2.375 | 2.18 | 0.091 | 42 | 2,100 |
| 2½ | 5125020 | 2.875 | 2.64 | 0.110 | 62 | 1,460 |
| 3 | 5130020 | 3.500 | 3.21 | 0.135 | 92 | 1,500 |
| 4 | 5140020 | 4.500 | 4.13 | 0.173 | 152 | 1,140 |
| 5 | 5150020 | 5.563 | 5.11 | 0.214 | 232 | 760 |
| 6 | 5160020 | 6.625 | 6.08 | 0.255 | 330 | 520 |
| 8 | 5480020 | 8.625 | 7.92 | 0.332 | 559 | 300 |
| SDR 21 - Pressure Rating 200 psi | | | | | | |
| ¾ | 5207520 | 1.050 | 0.92 | 0.060 | 12 | 8,000 |
| 1 | 5210020 | 1.315 | 1.18 | 0.063 | 16 | 5,600 |
| 1¼ | 5212520 | 1.660 | 1.49 | 0.079 | 25 | 4,400 |
| 1½ | 5215020 | 1.900 | 1.71 | 0.090 | 33 | 3,600 |
| 2 | 5220020 | 2.375 | 2.14 | 0.113 | 52 | 2,100 |
| 2½ | 5225020 | 2.875 | 2.58 | 0.137 | 76 | 1,460 |
| 3 | 5230020 | 3.500 | 3.15 | 0.167 | 113 | 1,500 |
| 4 | 5240020 | 4.500 | 4.05 | 0.214 | 186 | 1,140 |
| 6 | 5260020 | 6.625 | 5.96 | 0.316 | 405 | 520 |
| 8 | 5280020 | 8.625 | 7.76 | 0.410 | 684 | 300 |
| SDR 13.5 - Pressure Rating 315 psi | | | | | | |
| ½ | 5305020 | 0.840 | 0.71 | 0.062 | 10 | 7,200 |