

# PVC Gasketed PIP Pressure Pipe - West

## Conforms to ASTM D 2241

- Product manufactured with one integral gasketed bell per length
- Each spigot end is beveled to facilitate assembly and reference marked to indicate proper insertion depth
- Pipe is produced in 20-foot laying lengths
- Standard color is white

Trade Size	Part Number	Dimensions (in)		Minimum Wall Thickness (in)	Approximate Weight per 100' (lbs)	Crate Quantity (ft)
		Avg OD	Approx ID			
<b>SDR 51 - Pressure Rating 80 psi</b>						
6	1460020G	6.140	5.89	0.120	150	640
8	1480020G	8.160	7.82	0.160	267	360
10	14100020G	10.200	9.78	0.200	418	240
12	14120020G	12.240	11.73	0.240	604	160
15	14150020G	15.300	14.66	0.300	945	120
<b>SDR 41 - Pressure Rating 100 psi</b>						
6	1560020G	6.140	5.82	0.150	187	640
8	1580020G	8.160	7.74	0.199	330	360
10	15100020G	10.200	9.67	0.249	518	240
12	15120020G	12.240	11.61	0.299	748	160
15	15150020G	15.300	14.51	0.373	1,169	120
<b>SDR 32.5 - Pressure Rating 125 psi</b>						
6	1660020G	6.140	5.73	0.189	235	640
8	1680020G	8.160	7.62	0.251	415	360
10	16100020G	10.200	9.52	0.314	648	240
12	16120020G	12.240	11.43	0.377	934	160
15	16150020G	15.300	14.28	0.471	1,459	120