

# PVC IPS Gasketed Pressure Pipe - West

## Conforms to ASTM D 2241

- Certified to requirements of ANSI/NSF 61
- Product manufactured with one integral gasketed bell per length
- Each spigot end is beveled to facilitate assembly and reference marked to indicate proper insertion depth
- Pipe is produced in 20-foot laying lengths
- Standard color is white



Trade Size	Part Number	Dimensions (in)		Minimum Wall Thickness (in)	Approximate Weight per 100' (lbs)	Crate Quantity (ft)
		Avg OD	Approx ID			
<b>SDR 64 - Pressure Rating 63 psi</b>						
8	5980020G	8.625	8.34	0.135	240	300
<b>SDR 41 - Pressure Rating 100 psi</b>						
4	5040020G	4.500	4.27	0.110	101	1,140
5	5050020G	5.563	5.27	0.136	154	760
6	5060020G	6.625	6.28	0.162	219	520
8	5080020G	8.625	8.18	0.210	369	300
10	50100020G	10.750	10.19	0.262	558	240
12	50120020G	12.750	12.09	0.311	786	160
<b>SDR 32.5 - Pressure Rating 125 psi</b>						
4	5540020G	4.500	4.21	0.138	126	1,140
5	5550020G	5.563	5.20	0.171	192	760
6	5560020G	6.625	6.19	0.204	273	520
8	5580020G	8.625	8.06	0.265	463	300
10	55100020G	10.750	10.05	0.331	725	240
12	55120020G	12.750	11.92	0.392	1,019	160