

# PVC IPS Gasketed Pressure Pipe - East

## Conforms to ASTM D 2241

- Certified to requirements of ANSI/NSF 14
- Product manufactured with one integral gasketed bell per length
- Each spigot end is beveled to facilitate assembly and reference marked to indicate proper insertion depth
- Pipe is produced in 20-foot laying lengths
- Standard color is white



Trade Size	Part Number	Dimensions (in)		Minimum Wall Thickness (in)	Approximate Weight per 100' (lbs)	Crate Quantity (ft)
		Avg OD	Approx ID			
<b>SDR 26 - Pressure Rating 160 psi</b>						
3	5130020G	3.500	3.21	0.135	94	1,500
4	5140020G	4.500	4.13	0.173	156	1,140
6	5160020G	6.625	6.08	0.255	339	520
8	5180020G	8.625	7.92	0.332	559	300
<b>SDR 21 - Pressure Rating 200 psi</b>						
1½	5215020G	1.900	1.71	0.090	34	3,600
2	5220020G	2.375	2.14	0.113	53	2,100
2½	5225020G	2.875	2.58	.0137	78	1,460
3	5230020G	3.500	3.15	0.167	115	1,500
4	5240020G	4.500	4.05	0.214	191	1,140
6	5260020G	6.625	5.96	0.316	416	520
8	5280020G	8.625	7.76	0.410	704	300
<b>SDR 13.5 - Pressure Rating 315 psi</b>						
2	5320020G	2.375	2.01	0.176	80	2,100